


CoSF-R-ER-B-HP Ultra-narrow Linewidth Single Frequency Fiber Laser

Description:

Connet CoSF-R optimized traveling wave cavity ultra-narrow linewidth single-frequency fiber laser is a low-noise ultra-narrow linewidth fiber laser independently developed by patented technology. CoSF-R single-frequency fiber laser uses a unique "optimized traveling wave cavity" The design eliminates the standing wave space hole burning phenomenon which is easy to occur in the linear cavity fiber laser. In conjunction with the ultra-narrow bandwidth fiber filter designed by Connet, the single longitudinal mode output is selected and the single frequency operation of the fiber laser is guaranteed. The polarization control technology eliminates the polarization hole burning effect based on the all-fiber design, thereby achieving stable linear polarization, single longitudinal mode, and ultra-narrow linewidth single-frequency laser output.



CoSF-R ultra-narrow linewidth single-frequency fiber laser has excellent performance, the linewidth is less than 1kHz, and has ultra-low phase noise and frequency noise. The ultra-long laser cavity design makes the overall noise level of CoSF-R significantly lower than other commercial short-cavity single frequency lasers.

CoSF-R-ER-B-HP works in the 1.5um band, and the output power of the benchtop ultra-narrow linewidth single frequency fiber laser is up to 50W. Higher output power products can be provided on request. The standard wavelength is 1550.12nm, and the optional wavelength range is 1535-1605nm, such as the standard wavelength under the ITU framework.

Features:

- Ultra-narrow linewidth $< 1\text{kHz}$
- Ultra-low phase noise and frequency noise
- Ultra-low relative intensity noise (RIN)
- Stable single frequency, single polarization output
- No mode-hopping
- Benchtop all-in-one package
- PZT option

Applications:

- Distributed optical fiber sensing
- Coherent LiDAR
- Fiber optic hydrophone
- Laser spectroscopy
- Coherent communication
- Gas absorption measurement
- Cold atomic physics
- Other scientific research

Specifications:

Parameter	Unit	Specification		
		Min	Typ.	Max
Part no.		CoSF-R-ER-B-HP		
Center wavelength	nm	1530-1572nm fixed, other specify		
Output power	W	10W (HP1)	20W (HP2)	50W (HP3)
Laser output		CW, Single frequency & Single longitudinal mode		
Beam quality	M ²	<1.1	<1.3	<1.3
Linewidth	kHz	-	-	<<1
RIN peak frequency	kHz	40	70	100
RIN peak	dBc/Hz	-	-145	-140
RIN @10MHz	dBc/Hz	-	-155	-150
Phase noise (1m OPD)	urad/√Hz	100@10Hz		
	urad/√Hz	0.6@10kHz		
	urad/√Hz	0.1@100kHz		
SMSR (50pm resolution)	dB	55	60	-
Output polarization		Linear		
Polarization extinction ratio (PER)	dB	20	20	18
Output power stability	%	-	0.5	1
Output isolation	dB	35	-	-
Wavelength thermal tuning	nm	0.6	0.8	1.0
PZT wavelength modulation		Optional		
Modulation frequency (linear)	kHz	DC	10	20
Modulation wavelength range	GHz	-	>8	>10
Operating temperature	°C	15	-	40
Storage temperature	°C	-20	-	70
Power supply	V _{AC}	100-240		
Communication interface		RS232		
Output fiber type		PM1550	LMA PMF	LMA-PMF
Output fiber length	m	> 0.5		
Optical connector		FC/APC/CoL	CoL	CoL
Dimension	mm	430x450x105	510x480x150	
Weight	kg	<5	<15	<20

Ordering Information:

CoSF-R-ER-B-HP-<15xx>-<PW>-PMF/SMF-PZT-FA

PW: Output power: HP1, HP2, HP3

Options: 1. SMF output 2. Monitoring output 3. PZT fast modulation